

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) A method of controlling enablement/disablement of I/O requests from plural host computers to a disk device, said method comprising:
 - in said host computers,
 - transmitting access-right change commands to said disk device, said access-right change commands including one piece or plural pieces of information having I/O-enable/disable information and host identification information to correspond to each other in a one-to-one correspondence manner, said I/O-enable/disable information indicating whether or not said disk device will execute said I/O requests from said host computers, said host identification information identifying said respective host computers, and
 - issuing, to said disk device, said I/O requests to which said host computers have added said host identification information; and
 - in said disk device,
 - changing a batch of said I/O-enable/disable information on each host-computer basis in accordance with said access-right change commands from said host computers, and storing and holding said I/O-enable/disable information in an access-right management table,
 - identifying request-source host computers in response to said I/O requests from said host computers, and,

based on said host identification information and said I/O-
enable/disable information held in said access-right management table,
~~determining to enable or disable~~ enabling or disabling said I/O requests
to be executed on each host-computer's node basis.

2. (Currently Amended) The method according to Claim 1, comprising:
in said host computers,

transmitting path information to said disk device, said path
information having said host identification information and path
identification information correspond to each other, said path
identification information identifying all of logical paths from said host
computers to said disk device, and

issuing said I/O requests to which said host computers have
added said path identification information; and

in said disk device,

storing and holding said path identification information
transmitted from said host computers,

extracting said path identification information from said I/O
requests transmitted from said host computers, extracting said host
identification information corresponding to said path identification
information stored and held, and extracting said I/O-enable/disable
information with which said host identification information extracted
coincides, and

~~judging,~~ using the extracted said I/O enable/disable information,
~~whether to enable/disable to enable or disable~~ each I/O request for
said I/O requests on each host-computer's node basis.

3. (Currently Amended) The method according to Claim 1, comprising:
if an I/O-disable command is included in said I/O-enable/disable information in
said access-right change commands transmitted from said host computers,
then in said disk device,

extracting, from among said access-right change commands,
host identification information corresponding to said I/O-enable/disable
information with respect to all of I/O-disable commands included in said
same access-right change commands, and

updating said I/O-enable/disable information for host
identification information into an I/O-disable state, said host
identification information coinciding with said host identification
information extracted and being stored and held in said disk device,
and

if an I/O-enable command is included in said I/O-enable/disable information in
said access-right change commands transmitted from said host computers,
then in said disk device,

extracting, from among said access-right change commands,
host identification information corresponding to said I/O-enable/disable
information with respect to all of I/O-enable commands included in said
same access-right change commands, and

updating said I/O-enable/disable information for host
identification information into an I/O-enable state, said host
identification information coinciding with said host identification
information extracted and being stored and held in said disk device.

4. (Previously Presented) The method according to Claim 3, wherein
said processing of updating said I/O-enable/disable information for said host
identification information into said I/O-enable state is kept waiting for all of I/Os to be
completed, and is executed after completion of all of said I/Os, with said host
identification information being stored and held in said disk device, and all of said
I/Os being in processing in said host computers.

5. (Currently Amended) The method according to Claim 2, wherein
said disk device is configured to include plural logical disks resulting from
logically dividing an assembly of disk drives,
said host computers,

transmitting said access-right change commands to said disk
device, said access-right change commands including one piece or
plural pieces of information having said I/O-enable/disable information,
said host identification information and logical-disk identification
information correspond to each other, said I/O-enable/disable
information indicating whether or not said disk device will execute said
I/O requests from said host computers, said host identification

information identifying said respective host computers, and said logical-disk identification information identifying said logical disks, and

issuing, to said disk device, said I/O requests to which said host computers have added said logical-disk identification information and said path identification information;

said disk device,

changing a batch of said I/O-enable/disable information on each host-computer basis in accordance with said access-right change commands from said host computers, and storing and holding said access-right change commands,

extracting said path identification information from said I/O requests transmitted from said host computers, extracting said host identification information corresponding to said path identification information from said access-right change commands stored and held, and extracting said I/O-enable/disable information for which said host identification information extracted and logical-disk identification information on logical disks selected as targets of said I/O requests coincide with each other, and

~~judging,~~ using the extracted I/O-enable/disable information, ~~whether to enable/disable~~ to enable or disable each I/O request for said I/O requests on each host-computer's node basis.

6. (Previously Presented) The method according to Claim 5, wherein said extraction of said I/O-enable/disable information comprising:

extracting said logical-disk identification information and said host identification information from said access-right change commands, and
extracting said I/O-enable/disable information whose logical-disk identification information and host identification information coincide with said logical-disk identification information and said host identification information extracted.

7. (Currently Amended) A method of controlling enablement/disablement of I/O requests from plural host computers to a disk device, said method comprising,
wherein said host computers possess plural application processes, and
wherein said application processes including:

transmitting access-right change commands to said disk device,
said access-right change commands including one piece or plural pieces of information having I/O-enable/disable information and application-process identification information to correspond to each other in a one-to-one correspondence manner, said I/O-enable/disable information indicating whether or not said disk device will execute said I/O requests from said application processes, said application-process identification information identifying said respective application processes, and,

issuing, to said disk device, said I/O requests to which said application processes have added said application-process identification information; and

said disk device including operations of:

changing a batch of said I/O-enable/disable information on each application-process basis in accordance with said access-right change commands from said application processes, and storing and holding said I/O-enable/disable information in an access-right management table,

identifying request-source application processes in response to said I/O requests from said application processes, and,

based on said application-process identification information and said I/O-enable/disable information held in said access-right management table, ~~determining whether to enable/disable~~ enabling or disabling said I/O requests to be executed on each application-process's node basis.

8. (Currently Amended) An information processing system configured to control execution enablement/disablement of I/O requests from plural host computers to a disk device, comprising:

each of said host computers including:

an I/O request unit for issuing an I/O request to which said I/O request unit has added host identification information for identifying said respective host computers, and

an access-right change command unit for transmitting an access-right change command to said disk device, said access-right change command including one piece or plural pieces of information having I/O-enable/disable information and said host identification

information correspond to each other in a one-to-one correspondence manner, said I/O-enable/disable information indicating whether or not said disk device will execute said I/O requests from said host computers; and

said disk device including:

an access-right management table for storing and holding said access-right change commands from said host computers,

an access control unit for identifying request-source host computers of said I/O requests, and for judging whether to enable/disable said I/O requests to be executed on each host-computer basis, based upon said host identification information and said access-right management table, and

an access-right change unit that, in accordance with said access-right change commands from said host computers within said access-right management table, changes in a batch of said I/O-enable/disable information on each host-computer basis,

said disk device ~~judging whether to enable/disable~~ enabling or disabling said I/O requests on each host-computer's node basis, with said host computers being said I/O request sources.

9. (Currently Amended) The information processing system according to Claim 8, wherein

each of said host computers comprises a path-information transmission unit for transmitting path information to said disk device, said path information having

said host identification information and path identification information correspond to each other, said path identification information identifying all of logical paths from said host computers to said disk device,

said disk device comprising a path-information management table for storing and holding said path information transmitted from said path-information transmission unit in each of said host computers,

said I/O request unit issuing, to said disk device, said I/O request to which said I/O request unit has added said path identification information,

said access control unit

extracting said path identification information from said I/O requests transmitted from said host computers, making reference to said path-information management table to extract said host identification information corresponding to said path identification information extracted, and making reference to said access-right management table to extract said I/O-enable/disable information with which said host identification information extracted coincides, and

~~judging whether to enable/disable~~ enabling or disabling said I/O requests to be executed on each host-computer's node basis.